RANpump®

Ran® 2” (50.8 mm)

Aluminium Body Diaphragm Pump

Technical Specifications

Pump Code	EXF50M-A0	Pump Housing Material	Aluminium
Max. Flow Rate	596 lpm	Center Section Material	Aluminium
Max. Pump Speed	145 cpm	Max. Size Pumpable Solids	6.2 mm
Displacement per cycle	4.11 liter	Max. Suction Lift	9.5 m (Wet) 6 m (Dry)
Fluid Inlet- Outlet Size	2” NPT	Max. Opreating Tempreture	82 °C
Air Inlet Size	1/2”	Sound Level	82 dBa (at 5 bar)
Max. Fluid Working Pressure	8 bar	Diaphragm Material	Buna-N
Max. Air Consumption (at 5 bar)	2.3 m³/min	Check-Valve Material	Buna-N
Ratio	1:1	Weight	34.5 kg

Performance Curves



40% less air consumtion thanks to ECO+ series...

ATEX II 2gd IIb t135

Test Conditions: All tests are made with water.
Suction hose submerged in the fluid. Muffler not used.
All the values are shown are approximate and not binding.

Example: To pump 392 lpm against a discharge preasure of 3 bar, requires 7 bar and 2,3 m³/min air consumption.

Dimensions

A	507
B	407
C	322
D	622
E	375
F	192
G	12

All dimensions are in mm.