


Ran[®] 2" (50.8 mm)


316 Stainless Steel Body
Diaphragm Pump



Technical Specifications

Pump Code	F50M-SC1	Pump Housing Material	316 Stainless Steel
Max. Flow Rate	505 lpm	Center Section Material	Aluminium
Max. Pump Speed	145 cpm	Max. Size Pumpable Solids	6.2 mm
Displacement per cycle	3.48 liter	Max. Suction Lift	9.5 m (Wet) 6 m (Dry)
Fluid Inlet- Outlet Size	2" NPT	Max. Operating Temperature	104 °C
Air Inlet Size	1/2"	Sound Level	82 dBa (at 5 bar)
Max. Fluid Working Pressure	8 bar	Diaphragm Material	PTFE
Max. Air Consumption (at 5 bar)	2.04 m ³ /min	Check-Valve Material	PTFE
Ratio	1:1	Weight	65.5 kg

Performance Curves



40% less air consumption thanks to **ECO+** series...



Made in Turkey

Test Conditions: All tests are made with water. Suction hose submerged in the fluid. Muffler not used. All the values are shown are approximate and not binding.

Example: To pump 245 lpm against a discharge pressure of 2 bar, requires 4 bar and 1,2 m³/min air consumption.

Dimensions

A	507
B	407
C	322
D	622
E	375
F	192
G	12

All dimensions are in mm.

