PAGE 1440 APRIL 2011

Basic Pedestal

ACE

Self Priming Centrifugal Pump Model 83D20–B

Size 3" x 3"



Size: 3" x 3" (76 mm x 76 mm) NPT - Female.

Casing: Gray Iron 30.

Maximum Operating Pressure 87 psi (600 kPa).*

Semi-Open Type, Four Vane Impeller: Gray Iron 30.

Handles 3/4" (19,1 mm) Diameter Spherical Solids.

Impeller Shaft: Stainless Steel 316.

Replaceable Wear Plate: Carbon Steel 1026.

Pedestal: Gray Iron 30. Seal Plate: Gray Iron 30.

Seal Sleeve: Stainless Steel 304.

Flap Valve: Gray Iron 30 and Buna-N w/Nylon Reinforcement.

Radial and Thrust Bearings: Open Single Row Ball. Bearing Lubrication: SAE 30 Non-Detergent Oil.

Suction Flange: Gray Iron 25.

Gaskets: Vegetable Fiber.

Hardware: Standard Plated Steel.


Discharge Service Tee: Gray Iron 30.

Oil Level Sight Gage.

Optional Equipment: Strainer.


Consult Factory for Additional Options.

*Consult Factory for Applications Exceeding
Maximum Pressure and/or Temperature Indicated.









SEAL DETAIL Mechanical, Oil Lubricated, Double Floating, Self-Aligninig. Tungsten Titanium Carbide Rotating and Stationary Faces and Stainless Steel 316 Stationary Seat. Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Stainless Steel 303/304 Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F (71°C).*



THE GORMAN-RUPP COMPANY • MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA

www.grpumps.com

Specifications Subject to Change Without Notice


Printed in U.S.A.


Specification Data

SECTION 50, PAGE 1440

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: 120 LBS. (54,4 KG.) SHIPPING WEIGHT: 130 LBS.(58,9 KG.) EXPORT CRATE: 7.9 CU. FT. (0,22 CU. M.)







THE GORMAN-RUPP COMPANY • MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA


Specifications Subject to Change Without Notice

Printed in U.S.A.

Sec. 50

PAGE 1440.1 APRIL 2011

ACE





THE GORMAN-RUPP COMPANY ● MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED • ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice

Printed in U.S.A.